
Round plug connector, Series CON-RD 8946202812

General series information AVENTICS Series CON-RD Round plug connectors with cable

The AVENTICS Series CON-RD-with cable offers cables with round plug connectors for various types like M8x1, M12x1 or 7/8-16UNC and different cable length, optimized for our focused valves with M8x1 or M12x1 connection and electronic systems like AES and G3.





Technical data

Industry Type Cable Operational voltage Operating voltage AC max. Operating voltage DC, max. Electrical connection 1, type Electrical connection 1, thread size Electrical connection 1, number of poles Electrical connection 1, coding Cable exit Cable exit angle Industrial Round plug connectors with cable 60 V DC / 110 V AC 36 V DC 30 V AC Socket M12x1 8-pin A-coded straight 180°



Electrical connection 2, type	Plug
Electrical connection 2, thread size	M12x1
Electrical connection 2, number of poles	8-pin
Electrical connection 2, coding	A-coded
Cable exit	straight
Cable exit angle	180°
Number of wires	8
Shielding	shielded
Cable length	1 m
suitable for dynamic laying	suitable for dynamic laying
Protection class	IP67
Min. ambient temperature	-25 °C
Max. ambient temperature	80 °C
Max. current	1.5 A
Wire cross-section	0.25 mm²
Cable-Ø	6.6 mm
Weight	0.96 kg

Material


Housing material	
Seal material	
Material cable sheath	
Part No.	

Polyurethane Fluorocaoutchouc Polyurethane 8946202812

Technical information

The specified protection class is only valid in assembled and tested state.


Dimensions



L = length



Pin assignment, socket



Plug pin assignment

