Non-return valve, Series NR01

0821003002

Series NR01

2024-04-04

Series NR01

AVENTICS Series NR01, thanks to an array of connection options, the NR non-return valves can be screwed in separately and are also suitable for direct installation in piping.





Technical data

Industry Industrial
Type Poppet valve
Mounting thread-in
Compressed air connection 1 G 1/4

Compressed air connection type 1 Internal thread

Compressed air connection 2 G 1/4

Compressed air connection type 2 External thread Nominal flow Qn 1 to 2 1600 l/min

Min. working pressure 0.2 bar

Max. working pressure 10 bar

Min. ambient temperature -10 °C

Max. ambient temperature 70 °C

Min. medium temperature -10 °C

Medium Compressed air

Weight 0.04 kg

Material

Max. medium temperature

Housing material Brass

70 °C


Non-return valve, Series NR01

0821003002

Series NR01


2024-04-04

Surface housing Seal material Part No. Fig. 1 nickel-plated Acrylonitrile butadiene rubber 0821003002



	R1	L1	L2	L3	D2	SW1
0821003005	M5	20	5	5	2	8

Fig. 2



	R1	L1	L2	L3	SW1	SW2	SW3
0821003001	G 1/8	53	8	6	-	14	14
0821003002	G 1/4	66	12	9	19	-	17
0821003003	G 1/2	81	21	12	27	-	24

AVENTICS