


# Parallel gripper DHPC-16-A-NC-S-1

Part number: 8116798

FESTO



 General operating condition

## Data sheet

| Feature  | Value  |
|--|--|
| Size   | 16   |
| Stroke per gripper jaw                           | 3 mm   |
| Max. interchangeability                          | 0.2 mm   |
| Max. gripper jaw angular play ax, ay             | 0 deg  |
| Max. gripper jaw backlash Sz                     | 0 mm   |
| Rotational symmetry                              | ≤0.2 mm  |
| Pneumatic gripper repetition accuracy            | ≤0.02 mm   |
| Number of gripper jaws                           | 2  |
| Actuator system                                  | Pneumatic  |
| Mounting position                                | Any  |
| Mode of operation                                | Single-acting<br>Closed  |
| Gripper function                                 | Parallel   |
| Gripping force backup                            | During closing   |
| Structural design                                | Connection direction at side<br>Lever<br>Side mounting type for gripper fingers<br>Positively driven motion sequence |
| Guide  | Ball guide   |
| Position sensing                                 | For proximity sensor   |
| Symbol   | 00997348   |
| Operating pressure                               | 0.25 MPa ... 0.8 MPa   |
| Operating pressure                               | 2.5 bar ... 8 bar  |
| Operating pressure                               | 36.25 psi ... 116 psi  |
| Max. operating frequency of pneumatic gripper    | 3 Hz   |
| Min. opening time at 6 bar                       | 30 ms  |
| Min. closing time at 6 bar                       | 65 ms  |
| Operating medium                                 | Compressed air as per ISO 8573-1:2010 [7:4:4]  |
| Information on operating and pilot media         | Operation with oil lubrication possible (required for further use)   |
| Corrosion resistance class (CRC)                 | 0 - No corrosion stress  |
| LABS (PWIS) conformity                           | VDMA24364-B2-L   |
| Ambient temperature                              | -10 °C ... 60 °C   |
| Gripping force per gripper jaw at 6 bar, opening | 101 N  |
| Gripping force per gripper jaw at 6 bar, opening | 50.5 N   |
| Mass moment of inertia                           | 0.146 kgcm <sup>2</sup>  |
| Maximum force on gripper jaw Fz, static          | 49 N   |

| Feature                                  | Value   |
|--|---|
| Maximum torque on gripper jaw, Mx static | 0.34 Nm   |
| Maximum torque on gripper jaw, My static | 0.68 Nm   |
| Maximum torque on gripper jaw, Mz static | 0.34 Nm   |
| Product weight                           | 111 g   |
| Type of mounting                         | Optionally:<br>Direct mounting via through-hole<br>Direct fastening via thread<br>With through-hole and dowel pin<br>With internal thread and dowel pin |
| Pneumatic connection                     | M3  |
| Note on materials                        | RoHS-compliant  |
| Housing material                         | Aluminum, anodized  |
| Gripper jaw material                     | High-alloy stainless steel  |