

Datasheet

Suction cup BL30-2 Silicone FCM, 1/8" NPSF female, with mesh filter

Item number: BL30-2.21.04AG



- The silicone material complies with FDA 21 CFR 177.2600 & EU 1935/2004.
- Suitable for level adjustment.
- Lifting movement to separate small and thin objects.
- Less suitable when the lifting force is parallel to the surface of the object.

Technical data

Description	Unit	Value
Suction cup shape	-	Multibellows
Application	-	Bag handling, Food contact materials (FDA & EU), non-detectable
Suction cup design	-	Round
Characteristics	-	Bag handling, Food contact materials (FDA & EU), non-detectable
Material	-	Silicone (SIL)
Weight, min.	oz	0.25
Suction cup model	-	BL-2
Volume	in ³	0.61
Height	in	1.59
Outer diameter, min.	in	1.18
Fitting size	-	1/8"
Fitting option	-	Filter mesh
Fitting style	-	Female
Fitting type	-	NPSF-thread
Suction cup model	-	BL30-2
Movement, vertical max.	in	0.71
Curve radius, min.	in	0.31

Performance - Lifting forces


	Vertical (lb)	Parallel (lb)
BL30-2		
5.91 -inHg	1.57	
17.72 -inHg	4.047	

Material	Silicone (SIL FDA) 50° Shore
Name	Silicone (SIL FDA) 50° Shore
Color	Transparent
Temperature, min. °F	-40.0
Temperature max. °F	392.0
Hardness °Shore A	50

Material resistance

Alcohol	Good
Concentrated acids	Poor
Ethanol	n/a
Hydrolysis	Fair
Methanol	n/a
Oil	Poor
Oxidation	Excellent
Gasoline	Poor
Wear resistance	Good
Weather and ozone	Excellent

Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated)

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.

Accessories

04AB | Fitting G1/4" male, 30–40, with mesh filter
04AC | Fitting 1/4" NPT male, with mesh filter

Spare parts

04AG | Fitting 1/8" NPSF female, 30–40, with mesh filter

BL30-2.21 | Suction cup BL30-2 Silicone FCM