

# Datasheet

## Suction cup BX20P Polyurethane 60, G1/8" male / M5 female

Item number: BX20P.4E.02AF



- Suitable for level adjustment and for uneven and porous surfaces such as cardboard, etc.
- Dual hardness allowing strength and stability in conjunction with softness and flexibility.
- DURAFLEX® material features the elasticity of rubber in combination with the wear resistance of polyurethane.
- The DURAFLEX® material is mark-free.

### Technical data

Description	Unit	Value
Suction cup shape	-	Multibellows
Application	-	Dry sheet metal, Corrugated cardboard/Paperboard, Mark Free, Plastic injection molded parts
Suction cup design	-	Round
Characteristics	-	Dry sheet metal, Corrugated / cardboard, Mark free, Plastic injection molded parts
Material	-	Polyurethane (PU)
Weight, min.	oz	0.050
Suction cup model	-	BX-P
Volume	in <sup>3</sup>	0.071
Height	in	0.89
Outer diameter, min.	in	0.83
Fitting size	-	1/8", M5
Fitting option	-	Filter mesh
Fitting style	-	Female/Male
Fitting type	-	G-thread, M-thread
Suction cup model	-	BX20P PU60
Movement, vertical max.	in	0.30
Curve radius, min.	in	0.33

### Performance - Lifting forces


BX20P PU60	Vertical (lb)	Parallel (lb)
5.91 -inHg	1.079	0.43
17.72 -inHg	1.57	1.16
26.58 -inHg	2.47	1.38

<b>Material</b>	
Name	Polyurethane (PU60)
Color	Green transparent
Temperature, min.   °F	50.0
Temperature max.   °F	122.0
Hardness   °Shore A	60

#### Material resistance

Alcohol	n/a
Concentrated acids	Fair
Ethanol	Fair
Hydrolysis	Fair
Methanol	Poor
Oil	Excellent
Oxidation	Poor
Gasoline	Fair
Wear resistance	Excellent
Weather and ozone	Excellent

#### Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.

## **Accessories**

02AE | Fitting 5xM5 female  
BX20P.4K | Suction cup BX20P Polyurethane 30/60  
02AA | Fitting M5 female  
02AB | Fitting G1/8" male, with mesh filter  
02AC | Fitting 1/8" NPT male, with mesh filter  
02DD | Fitting G1/8" male/M5 female, with dual flow control valve

## **Spare parts**

02AF | Fitting G1/8" male/M5 female, with mesh filter  
BX20P.4E | Suction cup BX20P Polyurethane 60