

Suction cup BXF90P Polyurethane 60, T-slot with mesh filter

Item number: BXF90P.5Y.T2MR



Technical data

Description	Unit	Value
Suction cup shape	-	Bellows
Application	-	Oily sheet metal
Suction cup design	-	Round
Characteristics	-	Oily sheet metal
Material	-	Polyurethane (PU)
Weight, min.	oz	4.81
Suction cup model	-	BXF
Volume	in ³	10.98
Height	in	3.36
Outer diameter, min.	in	3.54
Outer diameter, actuated	in	3.63
Fitting size	-	None
Fitting option	-	Filter mesh
Fitting style	-	T-slot
Fitting type	-	G-thread
Fitting material	-	Al
Suction cup model	-	BXF90P Dry metal sheet
Movement, vertical max.	in	1.96
Curve radius, min.	in	6.30
Suction cup model	-	BXF90P Oily metal sheet
Movement, vertical max.	in	1.96
Curve radius, min.	in	6.30


Performance - Lifting forces

	Vertical (lb)	Parallel (lb)
BXF90P Dry metal sheet		
17.72 -inHg	37.99	18.88
26.58 -inHg	51.93	20.68
BXF90P Oily metal sheet		
17.72 -inHg	37.77	20.68
26.58 -inHg	50.58	23.16

Material	
Name	Polyurethane (PU60)
Color	Orange
Temperature, min. °F	50.0
Temperature max. °F	122.0
Hardness °Shore A	60

Material resistance	
Alcohol	n/a
Concentrated acids	Fair
Ethanol	Fair
Hydrolysis	Fair
Methanol	Poor
Oil	Excellent
Oxidation	Poor
Gasoline	Fair
Wear resistance	Excellent
Weather and ozone	Excellent

Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.