

Suction cup DCF52P Polyurethane 60, G3/8" female 17mm

Item number: DCF52P.5Y.G81W



Technical data


Description	Unit	Value
Suction cup shape	-	Deep Concave
Application	-	Oily sheet metal
Suction cup design	-	Round
Characteristics	-	Oily sheet metal
Material	-	Polyurethane (PU)
Weight, min.	oz	1.10
Suction cup model	-	DCF
Volume	in ³	0.50
Height	in	1.83
Height 2 (Actuated)	in	1.56
Outer diameter, min.	in	2.051
Outer diameter, actuated	in	2.17
Fitting size	-	3/8"
Fitting style	-	Female
Fitting type	-	G-thread
Fitting material	-	Al
Suction cup model	-	DCF52 Dry metal sheet
Movement, vertical max.	in	0.27
Curve radius, min.	in	1.10
Suction cup model	-	DCF52 Oily metal sheet
Movement, vertical max.	in	0.27
Curve radius, min.	in	1.10

Performance - Lifting forces

	Vertical (lb)	Parallel (lb)
DCF52 Dry metal sheet		
17.72 -inHg	16.19	11.47
26.58 -inHg	20.23	18.21
DCF52 Oily metal sheet		
17.72 -inHg	14.61	8.093
26.58 -inHg	19.33	11.47

Material	
Name	Polyurethane (PU60)
Color	Orange
Temperature, min. °F	50.0
Temperature max. °F	122.0
Hardness °Shore A	60
Material resistance	
Alcohol	n/a
Concentrated acids	Fair
Ethanol	Fair
Hydrolysis	Fair
Methanol	Poor
Oil	Excellent
Oxidation	Poor
Gasoline	Fair
Wear resistance	Excellent
Weather and ozone	Excellent

Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.