

Suction cup DCF52P Polyurethane 60, T-slot

Item number: DCF52P.5Y.T3W



Technical data

Description	Unit	Value
Suction cup shape	-	Deep Concave
Application	-	Oily sheet metal
Suction cup design	-	Round
Characteristics	-	Oily sheet metal
Material	-	Polyurethane (PU)
Weight, min.	oz	1.25
Suction cup model	-	DCF
Volume	in³	0.50
Height	in	1.10
Height 2 (Actuated)	in	0.83
Outer diameter, min.	in	2.051
Outer diameter, actuated	in	2.17
Fitting style	-	T-slot
Fitting material	-	Al (anodized)
Suction cup model	-	DCF52 Dry metal sheet
Movement, vertical max.	in	0.27
Curve radius, min.	in	1.10
Suction cup model	-	DCF52 Oily metal sheet
Movement, vertical max.	in	0.27
Curve radius, min.	in	1.10

Performance - Lifting forces


	Vertical (lb)	Parallel (lb)
DCF52 Dry metal sheet		
17.72 -inHg	16.19	11.47
26.58 -inHg	20.23	18.21
DCF52 Oily metal sheet		
17.72 -inHg	14.61	8.093
26.58 -inHg	19.33	11.47

Material	
Name	Polyurethane (PU60)
Color	Orange
Temperature, min. °F	50.0
Temperature max. °F	122.0
Hardness °Shore A	60

Material resistance

Alcohol	n/a
Concentrated acids	Fair
Ethanol	Fair
Hydrolysis	Fair
Methanol	Poor
Oil	Excellent
Oxidation	Poor
Gasoline	Fair
Wear resistance	Excellent
Weather and ozone	Excellent

Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.