


# Datasheet

## Suction cup F50MF Thermoelastic polyurethane

Item number: F50MF.40

- Suction cup of TPU, a mark free material that leaves no trace on the object being handled.
- Suitable for flat surfaces.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.



### Technical data

Description	Unit	Value
Suction cup shape	-	Flat
Application	-	Mark Free
Suction cup design	-	Round
Characteristics	-	Mark free
Material	-	TPE
Weight, min.	oz	0.35
Suction cup model	-	F-MF
Volume	in <sup>3</sup>	0.61
Height	in	0.69
Outer diameter, min.	in	2.087
Outer diameter, actuated	in	2.15
Fitting size	-	None
Fitting option	-	None
Fitting style	-	None
Fitting type	-	None
Suction cup model	-	F50MF
Movement, vertical max.	in	0.087
Curve radius, min.	in	3.74

### Performance - Lifting forces


	Vertical (lb)	Parallel (lb)
5.91 -inHg	5.51	6.97
17.72 -inHg	20.68	18.43
26.58 -inHg	31.70	24.055

<b>Material</b>	
Name	Thermoplastic Polyurethane (TPE-U)
Color	White transparent
Temperature, min.   °F	-4.0
Temperature max.   °F	176.0
Hardness   °Shore A	81

#### Material resistance

Alcohol	Good
Concentrated acids	Poor
Ethanol	n/a
Hydrolysis	Poor
Methanol	n/a
Oil	Excellent
Oxidation	Good
Gasoline	Poor
Wear resistance	Excellent
Weather and ozone	Excellent

#### Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.

## Accessories

05AF | Fitting 5x1/8" NPSF female, 50  
05AG | Fitting 1/8" NPSF female, 50, with mesh filter  
05CA | Fitting 1/8" NPSF female, 50, PA  
05AA | Fitting 1/8" NPSF female, 50  
05AD | Fitting G3/8" male, 50, with mesh filter  
05AE | Fitting 3/8" NPT male, with mesh filter  
05AB | Fitting G1/4" male, 50, with mesh filter  
05AC | Fitting 1/4" NPT male, with mesh filter  
05DA | Fitting 1/8" NPSF female, 50, with dual flow control valve  
05DB | Fitting G1/4" male, with dual flow control valve  
05DC | Fitting 1/4" NPT male, with dual flow control valve  
05DD | Fitting G3/8" male, 50, with mesh filter and dual flow control valve  
05DE | Fitting 3/8" NPT male, with dual flow control valve  
05DF | Fitting 5x1/8" NPSF female, 50, with dual flow control valve