

Suction cup F-BX25 Silicone G1/4" male composite, detectable, FCM

Item number: FBX25.DS40.G14MDC.00




Technical data

Description	Unit	Value
Suction cup shape	-	Multibellows
Application	-	Food contact materials (FDA & EU), detectable
Suction cup design	-	Round
Characteristics	-	Food contact materials (FDA & EU), detectable
Material	-	Silicone (SIL)
Load, torque, max.	lb ft	9.59
Weight, min.	oz	0.29
Suction cup model	-	F-BX
Volume	in ³	0.31
Height	in	1.65
Outer diameter, min.	in	1.024
Outer diameter, actuated	in	1.024
Fitting size	-	1/4"
Fitting option	-	None
Fitting style	-	Male
Fitting type	-	G-thread
Tightening torque, max.	lb ft	9.59
Fitting material	-	Composite
Suction cup model	-	F-BX25
Movement, vertical max.	in	0.61
Curve radius, min.	in	0.35

Performance - Lifting forces

F-BX25	Vertical (lb)	Parallel (lb)
2.95 -inHg	0.88	0.65
5.91 -inHg	1.55	1.034
11.81 -inHg	1.80	1.64

Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.

Accessories

- 02.07.147 | Fitting G1/4" Male, SS, F-BX25-50 P-D36
- 02.07.148 | Fitting 1/4"NPT Male, SS, F-BX25-50 P-D36
- 02.07.149 | Fitting G3/8" Male, SS, F-BX25-50 P-D36
- 02.07.150 | Fitting 3/8"NPT Male, SS, F-BX25-50 P-D36
- 02.07.151 | Fitting G1/4" Male, composite, F-BX25-50 P-D36
- 02.07.152 | Fitting 1/4"NPT Male, composite, F-BX25-50 P-D36
- 02.07.153 | Fitting G3/8" Male, composite, F-BX25-50 P-D36
- 02.07.154 | Fitting 3/8"NPT Male, composite, F-BX25-50 P-D36

Spare parts

- FBX25.DS40 | Suction cup F-BX25 Silicone detectable, FCM
- 02.07.151 | Fitting G1/4" Male, composite, F-BX25-50 P-D36