


Datasheet

Suction cup OF40x110P Polyurethane 40, thread insert G3/8" with mesh filter for Vacuum Gripper System (VGS)

Item number: OF40X110P.5C.G40M



- Suitable for flat and rough surfaces.
- Fair stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and give extra friction when the lifting force is parallel to the surface of the object.
- DURAFLEX® material features the elasticity of rubber in combination with the wear resistance of polyurethane.
- The DURAFLEX® material is mark-free.

Technical data

Description	Unit	Value
Suction cup shape	-	Flat
Application	-	Dry sheet metal, Corrugated cardboard/Paperboard, Plastic injection molded parts
Suction cup design	-	Oval
Characteristics	-	Dry sheet metal, Corrugated / cardboard, Plastic injection molded parts
Material	-	Polyurethane (PU)
Weight, min.	oz	1.69
Suction cup model	-	OF
Volume	in ³	1.28
Height	in	1.083
Length	in	4.45
Outer diameter, min.	in	4.45
Fitting size	-	3/8"
Fitting option	-	Filter mesh
Fitting style	-	Male
Fitting type	-	G-thread
Width	in	1.69
Suction cup model	-	OF40x110P PU40
Movement, vertical max.	in	0.12
Curve radius, min.	in	3.031

Performance - Lifting forces


OF40x110P PU40	Vertical (lb)	Parallel (lb)
5.91 -inHg	15.51	26.98
17.72 -inHg	45.64	51.71
26.58 -inHg	65.87	66.54

Material	
Name	Polyurethane (PU40)
Color	Red transparent
Temperature, min. °F	50.0
Temperature max. °F	122.0
Hardness °Shore A	40

Material resistance

Alcohol	n/a
Concentrated acids	Fair
Ethanol	Fair
Hydrolysis	Fair
Methanol	Poor
Oil	Excellent
Oxidation	Poor
Gasoline	Fair
Wear resistance	Excellent
Weather and ozone	Excellent

Dimensional drawings



Values specified in this data sheet are tested at (unless otherwise stated):

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.

Accessories

OF40X110P.5E | Suction cup OF40x110P Polyurethane 60 with collar for Vacuum Gripper System (VGS)

Spare parts

01.07.148 | Thread insert G3/8" male, with O-ring and mesh filter for Vacuum Gripper System (VGS)

OF40X110P.5C | Suction cup OF40x110P Polyurethane 40 with collar for Vacuum Gripper System (VGS)